


PRODUCT INFORMATION



Application Type	Inground Lights
Housing Type	Die Cast Aluminum, SS Ring
Colour Temperature	3500K, 6500K, 2700K, 3000K, 4000K, 6000K
Dimmable	Yes
Controls	Analog, Dali, On/off
Wattage Upto	15W, 18W
Size	dia: 160mm, height: 170mm
Driver	Remote
Input Voltage	24V



MODEL NO	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-BDA1600615A	15-18W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-240V	ON/OFF /Triac
ET-BDA1600615B	15W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-BDA1600618A	15-18W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-BDA1600618B	15-18W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-BDA1600618C	15-18W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-BDA1600618D	15-18W	6PCS CREE SMD	2200-6500K R/GB/Y/A	5°/8°/10°/12°/20°/28°/30°/40°/45°/60°/10°~22°/18°~85°/20°~60°	AC220-240V /AC110-130V	Triac/0-10V/DALI
ET-BDA16006115	15-18W	1PCS CREE COB	2700K-6500K	15°/24°/36°/60° (Lens)	AC220-240V /AC110-130V	ON/OFF /Triac/0-10V/DALI
ET-BDA16006118	15-18W	1PCS CREE COB	2700K-6500K	15°/24°/36°/60° (Lens)	AC220-240V /AC110-130V	ON/OFF /Triac/0-10V/DALI