


PRODUCT INFORMATION



Application Type	Luminn inground lights
Colour Temperature	3500K, 6500k, 2700K, 3000K, 4000K, 6000K
Housing Type	Die Cast Aluminum, SS Ring
Dimmable	Yes
Controls	Analog, Dali, On/off
Wattage Upto	6W, 8W, 10W, 12W
Size	dia: 132mm, height: 155mm
Driver	Inbuilt, Remote



MODEL NO	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL1320306	6W/8W	3PCS CREE SMD	220-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/71°/77°/22°/115°/55°/20°/60°	AC220-240V AC110-240V	ON/OFF r/inco-10V
ET-DIL1320310A	10W	3PCS CREE SMD	220-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/71°/77°/22°/115°/55°/20°/60°	AC220-240V	ON/OFF
ET-DIL1320310B	6-10W	3PCS CREE SMD	220-6500K R/G/B/Y/A	5°/8°/10°/12°/20°/25°/30°/40°/45°/60°/71°/77°/22°/115°/55°/20°/60°	AC220-240V	ON/OFF PWM 0-10V/DALI/DMX512
ET-DIL1320312A	6-12W	3PCS TYANSHINE SMD	Turnable White 2700K/6500K	25°/40°/60°	DC12V/DC24V DC36V/DC48V	PWM/DALI/DMX512
ET-DIL1320309	6-9W	3PCS TYANSHINE SMD	RGB 3in1 RGBW 4in1 5050/2835/3030	25°/40°/60°	DC12V/DC24V DC36V/DC48V	PWM/DMX512
ET-DIL1320312B	6-12W	3PCS TYANSHINE SMD	Turnable White 2700K/6500K	25°/40°/60°	DC12V/DC24V DC36V/DC48V	PWM/DMX512

