


## PRODUCT INFORMATION



<b>Application Type</b>	Inground Lights
<b>Colour Temperature</b>	3500K, 6500k, 2700K, 3000K, 4000K, 6000K
<b>Housing Type</b>	Die Cast Aluminum, SS Ring
<b>Dimmable</b>	Yes
<b>Controls</b>	Analog, Dali, On/off
<b>Wattage Upto</b>	15W, 18W
<b>Size</b>	dia: 160mm, height: 170mm
<b>Driver</b>	Inbuilt, Remote



Physical Dimension(MM)

MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL1600615A	15-18W	6PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20° 25°/30°/40°/45° 80°/10°/22° 15°/35°/20°/60°	AC220-240V /AC110-240V AC220-240V /AC110-130V	ON/OFF /Ttac
ET-DIL1600615B	15W	6PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20° 25°/30°/40°/45° 80°/10°/22° 15°/35°/20°/60°	AC220-240V /AC110-130V	Ttac/0-10V/DALI
ET-DIL1600618A	15-18W	6PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20° 25°/30°/40°/45° 80°/10°/22° 15°/35°/20°/60°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512
ET-DIL1600618B	15-18W	6PCS CREE SMD	2200-6500K RGB/Y/A	5°/8°/10°/12°/20° 25°/30°/40°/45° 80°/10°/22° 15°/35°/20°/60°	AC220-240V /AC110-130V	ON/OFF /0-10V/DALI/DMX512
ET-DIL1600618C	15-18W	6PCS TYANSHINE SMD	Turnable White 2700K/6500K	25°/40°/60°	DC12V/DC24V /DC36V/DC48V	PWM/DMX512
ET-DIL1600618D	15-18W	6PCS TYANSHINE SMD	RGB 3in1 RGBW 4in1 or 2500K-6500K	25°/40°/60°	DC12V/DC24V /DC36V/DC48V	PWM/DMX512

