


**PRODUCT INFORMATION**



<b>Application Type</b>	Inground Lights
<b>Colour Temperature</b>	3500K, 6500k, 2700K, 3000K, 4000K, 6000K
<b>Housing Type</b>	Die Cast Aluminum, SS Ring
<b>Dimmable</b>	Yes
<b>Controls</b>	Analog, Dali, On/off
<b>Wattage Upto</b>	42W, 48w, 54W
<b>Size</b>	dia: 248mm, height: 225mm
<b>Driver</b>	Inbuilt, Remote



MODEL NO.	POWER	LIGHT SOURCE	LED COLOR	BEAM ANGLE	INPUT VOLT	CONTROL
ET-DIL2480142	42W/48W/54W	1PCS CREE COB	2700K-6500K	15°/24°/38°/60° (Lens)	AC220-240V	ON/OFF
ET-DIL2480154	42-54W				AC110-240V	/Triac0-10V/DALI
ET-DIL2480142	42W/48W/54W	1PCS CREE COB	2700K-6500K	8-12°/22-26° (38-42°/37-43° Reflector Cup)	DC24VDC48V	ON/OFF
ET-DIL2480154	42-54W				AC220-240V	/0-10V/DALI/DMX512
ET-DIL2480142	42W/48W/54W	1PCS CREE COB	2700K-6500K	8-12°/22-26° (38-42°/37-43° Reflector Cup)	AC220-240V	ON/OFF
ET-DIL2480154	42-54W				AC110-240V	/Triac0-10V/DALI
ET-DIL2480142	42W/48W/54W	1PCS CREE COB	2700K-6500K	8-12°/22-26° (38-42°/37-43° Reflector Cup)	DC24VDC48V	ON/OFF
ET-DIL2480154	42-54W				AC220-240V	/0-10V/DALI/DMX512

